

CALL ALCAN FOR PRICING  
1-866-320-3756

**Model 721-FM  
with snow blower  
head, frame, and  
transfer case**



Model 960-FM

Large open flight  
auger with **shear bolt  
protection**

**No-Freeze-Up Chute**  
design seals out snow and  
freezing slush

Standard hydraulic  
**orbit motor  
chute rotator**

Efficient transfer case **rotates on  
its side** providing clearance for  
ease of installation and removal

**Adjustable frame system**  
fits all makes/model of  
tractors

**AVAILABLE IN...**

- 601-FM - 60"
- 721-FM - 72"
- 781-FM - 78"
- 841-FM - 84"
- 960-FM - 96"
- 1080-FM - 108"

Efficient 4-blade fan  
with **shear bolt  
protection**

Bolt-on, high-carbon  
steel cutting edge

Heavy-duty enclosed  
**drive chain**

**OPTIONS**

- Electric chute rotator (601-FM) in place of hydraulic chute rotator
- Hydraulic deflector
- Electric deflector
- Hardened skid shoes (601-FM/721-FM/781-FM) (Standard on 841-FM/960-FM/1080-FM)
- Optional truck loading chute (841-FM/960-FM/1080-FM)

**Ask About  
Our 8' and 9'  
rear mount blower  
models**



**STANDARD SPECIFICATIONS**

Model	1080-FM	960-FM	841-FM	781-FM	721-FM	601-FM
Stage	2	2	2	2	2	2
Width of Cut	108"	96"	84"	78"	72"	60"
Cutting Height	36"	36"	32"	29"	29"	27"
Auger Diameter	12" Top/18" Bottom	12" Top/18" Bottom	18" Open Flight	16" Open Flight	16" Open Flight	16" Open Flight
Fan Diameter	30" 4-Blade	30" 4-Blade	26" 4-Blade	22" 4-Blade	22" 4-Blade	20" 4-Blade
Discharge Chute	210° Hyd Rotator 1 2	210° Hyd Rotator 1 2	270° Hyd Rotator 1 2	270° Hyd Rotator 2	270° Hyd Rotator 2	270° Hyd Rotator 2
PTO Speed	540 or 1000 RPM	540 or 1000 RPM	540 or 1000 RPM	540 RPM	540 RPM	540 RPM
Casting Distance	up to 50'	up to 50'	up to 40'	up to 35'	up to 35'	up to 30'
Minimum Horsepower	85	85	50	30	30	20
Driveline Series	55	55	35	35	35	12
Cutting Edge	5/8" x 6" Bolt-on	5/8" x 6" Bolt-on	1/2" x 4" Bolt-on	1/2" x 4" Bolt-on	1/2" x 4" Bolt-on	3/8" x 3" Bolt-on
Skid Shoes	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable	Adj. & Replaceable
Shipping Weight	3300#	3245#	2190#	1660#	1630#	1050#

1 Truck loading chute with deflector control is optional 2 Includes deflector & 3-position linkage. Hydraulic or electric is optional.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE